

Product Details

Table Top Power Supply

Cable Management

Painted steel box with oxidation. Top panel and lid produced from aluminium-magnesium alloy.
Pneumatic operated top lid – opens to 45°.
Mechanical latching mechanism (German) locks and releases top lid with finger pressure.

Any combination of sockets can be installed to customer's requirements.
Power socket: universal, Euro, U.K., USA, Africa, Australia, China, Hong Kong
110v – 240v, 50/60Hz 10amp
Network/data/phone connector
Video – audio, microphone
VGA, USB, HDMI
Available in any multiples.

Sealed bottom section sockets match top lid sockets.
Simple installation. Set of two brackets supplied to secure cable box to bottom surface of table.
No screws required.
Connect appropriate cables to socket, then to related power supply and related equipment.
Note: Accessory cables not supplied.
All components have CE, TUV, UL, RoHS certification.

Additional details

Table thickness. Minimum 2cm, maximum 6cm.

Template 'A' 148x121mm for product code 1770025

Template 'C' 122x180cm for product code 1770026

Note: Longer dimension is width or front position of cable box insertion into table cut out.
Depth is standard for all models, 150mm.

Weight 1.5 kgs

Finish colour: matte black

Operating temperature 10°-35°C

Humidity limit 90% non-condensing

Accessories: 2 mounting clamps with wing nuts – template and instruction literature.

Application Diagram

