

EB-L1715S

DATASHEET / BROCHURE



Versatile 15,000-lumen 3LCD laser projector, offering outstanding fit and forget reliability as well as sharp, vivid imagery with SXGA+ resolution.

Exceptionally bright 15,000-lumen SXGA+ performance combines with rich, vivid colours to make the EB-L1715S installation laser projector an ideal option for large rooms and venues. As well as reliable fit and forget performance, it offers very flexible installation, creating a dedicated solution for scenarios where only maximum performance and durability will do.

Laser-sharp images

Ensure that your presentations, images and video pack a punch with the vivid, sharp projection offered by this 3LCD laser projector. Designed for larger venues, its high resolution SXGA+ images are vivid and bright, even in daylight, while inorganic phosphor wheel technology provides superior light and heat resistance to deliver excellent reliability that lasts for up to 83,000 hours¹.

Flexible positioning

Thanks to a wide range of motorised lenses, including optional ultra-short-throw (UST) lens, the projector benefits from true 360° installation flexibility, allowing it to be placed virtually anywhere - without loss of brightness or distortion of image. The projector also has a built-in camera to ensure accurate calibration and capture diagnostic images (this can be fully disabled to prevent remote access).

Versatile new software

All models in the EB-L1000 series can take advantage of free Epson Professional Projector Tool software from December 2017. It allows you to set up multi-projector installations straight out of the box, simply and quickly, as well as utilising advanced techniques such as projection-mapping and edge-blending.

Quick set-up

Get started quickly thanks to a lens memory function which stores projector settings such as image position, focus and zoom, for prompt access when projecting images in different aspect ratios, or using different lenses.

KEY FEATURES

- **Laser light source technology**
Outstanding brightness and colour, with fit and forget reliability
- **Sharp, clear imagery**
Outstanding clarity and detail for crisp images and readable text
- **Versatile new software**
Set up multiple projector installations and utilise advanced projection techniques
- **Flexible 360° installation**
True flexibility without distortion or loss of brightness
- **Added peace of mind**
Product comes with five-year, 20,000-hour warranty



EPSON
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY

| | |
|-------------------|------------------------|
| Projection System | 3LCD Technology |
| LCD Panel | 1.06 inch with C2 Fine |

IMAGE

| | |
|------------------------------|---|
| Color Light Output | 15,000 Lumen- 10,500 Lumen (economy) In accordance with ISO 21118:2013 |
| White Light Output | 15,000 Lumen - 10,500 Lumen (economy) In accordance with ISO 21118:2013 |
| Portrait Colour Light Output | 15,000 lm |
| Portrait White Light Output | 15,000 lm |
| Resolution | SXGA+ (14000 x 1050), 4:3 |
| Aspect Ratio | 4:3 |
| Contrast Ratio | 2,500,000 : 1 |
| Native Contrast | 2,000 : 1 |
| Light source | Laser |
| Laser Light source | 20,000 hours Durability High, 30,000 hours Durability Eco |
| Keystone Correction | Manual vertical: $\pm 45^\circ$, Manual horizontal $\pm 30^\circ$ |
| Colour Reproduction | Upto 1.07 billion colours |

OPTICAL

| | |
|-------------------------------|---|
| Throw Ratio | 1.62 - 2.65:1 |
| Zoom | Motorized, Factor: 1 - 1.6 |
| Projection Lens Zoom Ratio | 1.62 - 2.56 : 1 |
| Lens | Optical |
| Lens Shift | Motorized - Vertical $\pm 55\%$, horizontal $\pm 19\%$ |
| Lens position memory | 10 positions |
| Screen Size | 60 inches - 500 inches |
| Projection Distance Wide | 1.9 m - 16.7 m |
| Projection Distance Tele | 3.2 m - 27.1 m |
| Projection Distance Wide/Tele | 1.93 m - 27.1 m |
| Projection Lens F Number | 1.8 - 2.3 |
| Projection Lens Focal Length | 36 mm - 57.35 mm |
| Projection Lens Focus | Motorized |
| Interchangeable Lens | Yes |

CONNECTIVITY

| | |
|-----------------------|---|
| Interfaces | Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), Wireless LAN b/g/n (2.4GHz) (optional) |
| Epson iProjection App | Ad-Hoc / Infrastructure |

ADVANCED FEATURES

| | |
|-------------------|--|
| Security | Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection |
| Other features | Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory |
| Video Color Modes | Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 |
| Projector control | via: AMX, Crestron, Extron |

GENERAL

| | |
|-------------------------|--|
| Power consumption | 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt |
| Supply Voltage | AC 100 V - 240 V, 50 Hz - 60 Hz |
| Product dimensions | 586 x 492 x 211 mm (Width x Depth x Height) |
| Product weight | 24 kg |
| Noise Level | Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) |
| Supported Temperature | Storage -10° C - 60° C |
| Supported Humidity | Operation 20% - 80%, Storage 10% - 90% |
| Included Software | EasyMP Monitor, EasyMP Multi PC Projection |
| Options | HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit |
| Room Type / Application | Meeting room / Classroom, Projection Mapping, Rental / Staging, Visitor Attraction |
| Positioning | Ceiling Mounted |
| Colour | Black |

OTHER

| | |
|----------|--------------------------------|
| Warranty | 60 months Carry in or 20,000 h |
|----------|--------------------------------|

EB-L1715S

WHAT'S IN THE BOX

- Remote control incl. batteries
- Quick Start Guide
- Power and signal cable (3 m)
- Computer cable
- Cable cover
- CD Manual

OPTIONAL ACCESSORIES

- Air Filter - ELPAF51
V13H134A51
- Ceiling Mount - ELPMB47 Low EB-G7000/L1000
V12H802010
- Ceiling Mount - ELPMB48 High EB-G7000/L1000
V12H803010
- HDBaseT Transmitter - ELPHD01
V12H547041
- Wireless LAN Adapter - ELPAP10
V12H731P01
- Stacking Frame - ELPMB59 - L1000 Series (EVO)
V12H996B59

EB-L1715S

OPTIONAL LENSES

- Lens - ELPLU03S - L & G Series ST off axis 1
V12H004UA3
- Lens - ELPLL08 - Long throw - G7000/L1000 series
V12H004L08
- Lens - ELPLM10 - Mid throw 3 - G7000/L1000 series
V12H004MOA
- Lens - ELPLM11 - Mid throw 4 - G7000/L1000 series
V12H004MOB
- Lens - ELPLM15 - Mid Throw L1500/L1700 Series
V12H004MOF
- Lens - ELPLU03 - G7000 & L1000 Series ST off axis 1
V12H004U03
- Lens - ELPLU04 - G7000 & L1000 Series ST off axis 2
V12H004U04
- Lens - ELPLW05 - G7000 & L1000 Series wide zoom 1
V12H004W05
- Lens - ELPLW06 - L1500U/1505U wide zoom 2
V12H004W06
- Lens - ELPLX02 - UST Lens L1500/1700 Series
V12H004X02
- Lens - ELPLW08 - Wide throw
V12H004W08

LOGISTICS INFORMATION

| | |
|-------------------|---------------|
| SKU | V11H890140 |
| EAN code | 8715946645988 |
| Country of Origin | China |
| Layer | 1 Units |
| Layer Block | 1 Units |

For more information please contact:

Home users: 0343 90 37766
Business users*: 0871 42 37766
Republic of Ireland: 01 436 7742
Or visit us at <https://www.epson.co.uk/contactus>
* 10p per minute plus network extras.

Web: www.epson.co.uk
www.epson.ie

1. - Laser life of up to 83,000 hours in custom mode.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.
Last extracted: 2020-01-28

EPSON[®]