LightScene EV-100



DATASHEET / BROCHURE

















2,000-lumen WXGA accent lighting projector in white, with a low visual noise design, ideal for retail displays, galleries and museums.

Add movement and life to your retail displays or exhibitions with a low visual noise projector that blends in beautifully to any environment, and blurs the line between lighting and projection with 2,000-lumen brightness and WXGA sharpness.

A discreet attention-grabber

The LightScene EV-100 allows you to to create instantly appealing visuals with sharp WXGA resolution and 2,000-lumen brightness. Yet thanks to its low visual noise white casing, it can be used where a traditional projector would stand out, such as window displays and as part of exhibitions.

Simple, flexible implementation

A light, flexible design means the EV-100 can be installed in a variety of ways, from a traditional ceiling mount to a freestanding floor mount, or attached to an existing lighting track like a spotlight¹. It can also be mounted at and project from any angle, including portrait. The projector can be used as a traditional spotlight for when simple lighting effects are needed.

Easy to program and use

The EV-100 comes with Epson Projector Content Manager Software for quick, easy set-up without specialist installation. Playlists can easily be loaded via SD Card and changed using remote control by employees without the need for a computer. The projector can also use advanced techniques such as edgeblending to achieve stunning results in larger spaces that require multiple-unit installations.

Fit and forget reliability

A five-year, 20,000-hour warranty, coupled with Epson's durable, reliable inorganic phosphor wheel technology means that EV-100 projectors can be installed and forgotten about, and don't require regular maintenance.

KEY FEATURES

- Discreet signage projector
 Low visual noise white casing won't grab the spotlight
- Sharp, vivid projection
 2,000-lumen brightness and detailed
 WXGA resolution
- Flexible installation
 Can be ceiling-mounted, floor-standing or attached to a lighting track
- Easy playlist loading
 Playlist can be loaded from an SD Card
 without the need for a computer
- Fit and forget reliability

 Durable Epson technology supported by a five-year 20,000-hour warranty





PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology LCD Panel 0.59 inch with C2 Fine

IMAGE

Color Light Output 2,000 Lumen-1,000 Lumen (economy) In accordance with ISO 21118:2013
White Light Output 2,000 Lumen - 1,000 Lumen (economy) In accordance with ISO 21118:2013

Portrait Colour Light Output 2,000 lm Portrait White Light Output 2,000 lm

Resolution WXGA, 1280 x 800, 16:10

 Aspect Ratio
 16:10

 Contrast Ratio
 2,500,000 : 1

 Native Contrast
 1,200 : 1

 Light source
 Laser

Laser Light source 20,000 hours Durability High, 30,000 hours Durability Eco

Keystone Correction Manual vertical: \pm 45 °, Manual horizontal \pm 40 °

Colour Reproduction 16.77 million colours

OPTICAL

Throw Ratio 1.38 - 2.19:1

Zoom Motorized, Factor: 1 - 1.58

Projection Lens Zoom Ratio 1.38 - 2.19 : 1
Lens Optical

Screen Size 30 inches - 133 inches

Projection Distance Wide 0.9 m - 4 m
Projection Distance Tele 1.4 m - 6.3 m
Projection Distance Wide/Tele 0.88 m - 6.34 m
Projection Lens F Number 1.51 - 1.92
Projection Lens Focal Length 18.2 mm - 28.4 mm
Projection Lens Focus Motorized

CONNECTIVITY

Interfaces USB 2.0 Type A, USB 2.0 Type B (Service Only), Ethernet interface (100 Base-TX / 10 Base-T),

Wireless LAN b/g/n (2.4GHz), HDMI in, Stereo mini jack audio out, SD Card Slot, SD Card

playback

ADVANCED FEATURES

Security Wireless LAN security, Password protection

Other features Digital zoom, Horizontal and vertical keystone correction, Quick Corner

Video Color Modes Dynamic
Projector control via: Crestron

GENERAL

Power consumption 170 Watt, 118 Watt (economy), 0.3 Watt (standby)

Supply Voltage AC 100 V - 240 V, 50 Hz - 60 Hz

Product dimensions (default 530 x 470 x 250 mm (Width x Depth x Height)

position)

Dimensions: Projection Unit Ø175 x 260 mm (Depth)

Dimensions: Power Supply 361 x 110 x 65 mm (Width x Depth x Height)

Product weight 5 kg
Direct Mount weight 1.9 kg

Noise Level

Normal: 34 dB (A) - Economy: 22 dB (A)

Supported Temperature

Operation 5° C - 40° C, Storage -10° C - 60° C

Supported Humidity

Operation 20% - 80%, Storage 10% - 90%

Room Type / Application Signage / Retail, Visitor Attraction

Colour White

OTHER

Warranty 60 months Carry in or 20,000 h

Optional warranty extension available

LightScene EV-100

WHAT'S IN THE BOX

- Cable cover
- Direct mount unit
- HDMI Cable Clamp
- Power cable
- Remote control incl. batteries
- User's Manual Set



OPTIONAL ACCESSORIES

 Lighting Track Mount - ELPMB54W - EV-100 V12H933W40

 Floor Stand - ELPMB55W - EV-100 V12H888W10

LOGISTICS INFORMATION

sku	V11H868041
EAN code	8715946647494
Country of Origin	China



For more information please contact:

Home users: 0343 90 37766
Business users*: 0871 42 37766
Republic of Ireland: 01 436 7742
Or visit us at https://www.epson.co.uk/contactus
* 10p per minute plus network extras.

Web: www.epson.co.uk www.epson.ie

1. Floor stand and lighting track are purchasable options.

LightScene EV-100

