

AX Series

A feature rich stylish 4K touchscreen that will run portrait or landscape – NOW in 65" and 75"



4K Ultra HD resolution

Bright, sharp and precise definition touchscreens ensuring engagement with your audience



Access all the latest apps within the Aptoids app store



Add value and peace of mind with the most comprehensive 5 year de-install and re-install warranty



Simple to use whiteboarding to make every session great



Running the latest version of Android 7.1.2 to give you all the great features



With bi-directional touch, mirror any device to your M-Touch and have participants collaborating quickly



Design your space with our first ever touchscreen that has the ability to run in portrait or landscape



Easy to set up, design your own launch page to suit your organisation

Distributed exclusively by Sahara AV

info@mymtouch.com

Specifications

Product code: 1090010 Product code: 1090011

DISPLAY	65"	75"
Mainboard Model	17MB150VS	17MB150VS
H-Freq	135KHz	135KHz
Max. Pixel Freq.	81MHz	78MHz
V-Freq	120Hz	60Hz
Diagonal Screen Size (inch)	65"	75"
Backlight	DIRECT LED	DIRECT LED
Panel Technology	VA	IPS
Panel Type	16/7	16/7
Orientation	Landscape / Portrait	Landscape / Portrait
Panel Resolution	3840 x 2160	3840 x 2160
Active Area (mm – H x V)	1429 x 804	1650 x 928
Brightness (cd/m ²)	350	360 ± %20
Contrast Ratio	1200	1200
Panel Life Typ. (hours)	30,000 / 50,000	30,000 / 50,000
Viewing Angle (°) Up/Down, Left/Right	178°	178°
Response Time (ms)	6	8
Display Colours	8bit, 16.7 M colours	10bit(D), 1.07Billon colours
Usage (Indoor/Outdoor)	INDOOR	INDOOR
MONITOR CONNECTIVITY	65"	75"
HDMI Input	1	1
HDMI Support Type	2.0	2.0
DisplayPort Input	1	1
DisplayPort Output	1	1
DisplayPort Support Type	1.2a	1.2a
VGA	Yes	Yes
USB 2.0	1	1
USB 3.0	1	1
Micro USB for Touch connectivity	Yes	Yes
RS232	9 pin DSUB	9 pin DSUB
LAN (Control)	Yes	Yes
RCA (L/R) Input	Yes	Yes
Headphone Output Line out Jack		
	Yes	Yes
Speakers	Yes 2 x 8 watt	Yes 2 x 8 watt
Speakers ANDROID		
	2 x 8 watt	2 x 8 watt
ANDROID	2 x 8 watt 65"	2 x 8 watt 75"
ANDROID OS Version	2 x 8 watt 65" Android 7.1.2	2 x 8 watt 75" Android 7.1.2
ANDROID OS Version Kernel Version	2 x 8 watt 65" Android 7.1.2 3,10.86	2 x 8 watt 75" Android 7.1.2 3,10.86
ANDROID OS Version Kernel Version Memory	2 x 8 watt 65" Android 7.1.2 3,10.86 2GB DDR4	2 x 8 watt 75" Android 7.1.2 3,10.86 2GB DDR4
ANDROID OS Version Kernel Version Memory Storage	2 x 8 watt 65" Android 7.1.2 3,10.86 2GB DDR4 8GB	2 x 8 watt 75" Android 7.1.2 3,10.86 2GB DDR4 8GB
ANDROID OS Version Kernel Version Memory Storage SD card support	2 x 8 watt 65" Android 7.1.2 3,10.86 2GB DDR4 8GB Yes (up to 1TB)	2 x 8 watt 75" Android 7.1.2 3,10.86 2GB DDR4 8GB Yes (up to 1TB)
ANDROID OS Version Kernel Version Memory Storage SD card support USB 2.0	2 x 8 watt 65" Android 7.1.2 3,10.86 2GB DDR4 8GB Yes (up to 1TB) 2	2 x 8 watt 75" Android 7.1.2 3,10.86 2GB DDR4 8GB Yes (up to 1TB) 2
ANDROID OS Version Kernel Version Memory Storage SD card support USB 2.0 USB 3.0	2 x 8 watt 65" Android 7.1.2 3,10.86 2GB DDR4 8GB Yes (up to 1TB) 2 No	2 x 8 watt 75" Android 7.1.2 3,10.86 2GB DDR4 8GB Yes (up to 1TB) 2 No
ANDROID OS Version Kernel Version Memory Storage SD card support USB 2.0 USB 3.0	2 x 8 watt 65" Android 7.1.2 3,10.86 2GB DDR4 8GB Yes (up to 1TB) 2	2 x 8 watt 75" Android 7.1.2 3,10.86 2GB DDR4 8GB Yes (up to 1TB) 2 No Yes
ANDROID OS Version Kernel Version Memory Storage SD card support USB 2.0 USB 3.0 RJ45 WORKING CONDITIONS	2 x 8 watt 65" Android 7.1.2 3,10.86 2GB DDR4 8GB Yes (up to 1TB) 2 No Yes 65"	2 x 8 watt 75" Android 7.1.2 3,10.86 2GB DDR4 8GB Yes (up to 1TB) 2 No Yes Yes 75"

MECHANICAL 65" 75" Size (mm - WxHxD) 1507 x 882 x 120 1731 x 1008 x 119 Weight (kg) 43 80 Packed Width (mm -WxHxD) 1620 x 1006 x 190 1990 x 1227 x 265 Packed Weight (kg) 54 90 VESA - W x H (Screw Type) 400 x 400 M6 600 x 400 M8 POWER 65" 75" Power supply 110 VAC - 240 VAC - 50/60 Hz 110 VAC - 240 VAC - 50/60 Hz Active Standby Consumption 14W 22.61 W Standby Consumption 74W 244 W Mains Plug Type EU + UK EU + UK TOUCH TECHNOLOGY 65" 75" Type of Touch Tech. And Supported Point Infrared (IR) Tech Infrared (IR) Tech Supported Points 10 10 20
Packed Width (mm -WxHxD)1620 x 1006 x 1901990 x 1227 x 265Packed Weight (kg)5490VESA - W x H (Screw Type)400 x 400 M6600 x 400 M8POWER65"75"Power supply110 VAC - 240 VAC - 50/60 Hz110 VAC - 240 VAC - 50/60 HzActive Standby Consumption14W22.61 WStandby Consumption<0.5W
Packed Weight (kg)5490VESA - W x H (Screw Type)400 x 400 M6600 x 400 M8POWER65"75"Power supply110 VAC - 240 VAC - 50/60 Hz110 VAC - 240 VAC - 50/60 HzActive Standby Consumption14W22.61 WStandby Consumption<0.5W
VESA - W x H (Screw Type)400 x 400 M6600 x 400 M8POWER65"75"Power supply110 VAC - 240 VAC - 50/60 Hz110 VAC - 240 VAC - 50/60 HzActive Standby Consumption14W22.61 WStandby Consumption<0.5W<0.5WConsumption On74W244 WMains Plug TypeEU + UKEU + UKTOUCH TECHNOLOGY65"75"Type of Touch Tech. And Supported PointsInfrared (IR) TechInfrared (IR) TechSupported Points1010
POWER65"75"Power supply110 VAC - 240 VAC - 50/60 Hz110 VAC - 240 VAC - 50/60 HzActive Standby Consumption14W22.61 WStandby Consumption<0.5W
Power supply110 VAC - 240 VAC - 50/60 Hz110 VAC - 240 VAC - 50/60 HzActive Standby Consumption14W22.61 WStandby Consumption<0.5W
Power supply50/60 Hz50/60 HzActive Standby Consumption14W22.61 WStandby Consumption<0.5W
Standby Consumption<0.5W<0.5WConsumption On74W244 WMains Plug TypeEU + UKEU + UKTOUCH TECHNOLOGY65"75"Type of Touch Tech. And Supported PointsInfrared (IR) TechInfrared (IR) TechSupported Points1010SensitivityAny touch with finger, Any touch with finger,Any touch with finger,
Consumption On74W244 WMains Plug TypeEU + UKEU + UKTOUCH TECHNOLOGY65"75"Type of Touch Tech. And Supported PointsInfrared (IR) TechInfrared (IR) TechSupported Points1010Sensitivity.Any touch with finger, Any touch with finger,Any touch with finger,
Mains Plug Type EU + UK EU + UK TOUCH TECHNOLOGY 65" 75" Type of Touch Tech. And Supported Point Infrared (IR) Tech Infrared (IR) Tech Supported Points 10 10 Sensitivity Any touch with finger, Any touch with finger,
TOUCH TECHNOLOGY65"75"Type of Touch Tech. And Supported PointInfrared (IR) TechInfrared (IR) TechSupported Points1010SensitivityAny touch with finger, Any touch with finger,Any touch with finger,
Type of Touch Tech. And Supported Point Infrared (IR) Tech Infrared (IR) Tech Supported Points 10 10 Sensitivity Any touch with finger, Any touch with finger,
And Supported Point Immated (ik) Fech Supported Points 10 Sensitivity Any touch with finger,
Sensitivity, Any touch with finger, Any touch with finger,
Connectivity HID, TUIO, Flash HID, TUIO, Flash
Supported OS and Applications Windows®7,Windows®8, Mindows®10, Vista, XP, Mac® OS, Linux, Android Mac® OS, Linux, Android
Orientation Landscape / Portrait Landscape / Portrait
Calibration N/A HID compliant N/A HID compliant
Accuracy %90 < %90 <
Reporting Rate Up to 450 fps Up to 450 fps
Glass Type Anti Glare (AG), Tempered Anti Glare (AG), Tempered
Frame Rate Up to 450 fps Up to 450 fps
Communication USB 2.0 USB 2.0
Power Supply Mode USB USB
Supply Voltage DC 5V +/- 5% DC 5V +/- 5%
Average Current <400mA <400mA
Response Time <10ms <10ms
Touch Accuracy +/-2mm (over 90% area) +/-2mm (over 90% area)
Object Sizes for Touch 5mm 5mm
Touch Durability Unlimited Unlimited
ACCESSORIES 65" 75"
Remote Control Yes Yes
Remote Control Battery (Type) AAA AAA
IR Extender Cable Yes Yes
Add USB Extension Hub Yes Yes
Power Lead Yes Yes
Quick Start User Guide Yes Yes
Cable management clips n/a Yes
Back USB security cover n/a Yes