

Model Name

MW632ST Digital Projector

Unique selling point	Trade Mark
 SmartEco Power Saving technology 	
* Up to I 0000hours Long lamp life	
1 2 UDMI Ports and I MUI	

- 2 HDMI Ports and I MHL
 <0.5W standby mode
- * Short Throw Ratio

.





Projection System	DLP			
Native Resolution	WXGA (1280x800)			
Brightness	3200AL			
Contrast Ratio	13000:1			
Display Color	1.07 Billion Colors			
	F/#=2.6~2.78			
Lens	f=10.2~12.24			
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)			
Throw Ratio	0.72~0.87(87"±3% @ 1.36m)			
Image Size (Clear Focus/ Maximum)	60"~120" / 300"			
Zoom Ratio	1.2:1			
Lamp Type	196W			
Lamp(Normal/Economic/SmartEco Mode)*	4000/6000/6500/10000 hours			
Keystone Adjustment	ID, Vertical +/- 30 degrees			
	105% ±5%			
Projection Offset				
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200)	* RB= Reduced blanking		
Horizontal Frequency	15K~102KHz			
Vertical Scan Rate	24~120Hz			
Compatibility	HDTV Compatibility	480i, 480p, 576i, 576p,	720p, 1080i, 1080p	
	Video Compatibility	NTSC, PAL, SECAM	uential JU for resolutions up to YVAGA, PC: 60HZ IOP-DOttom JU for	
	3D Compatibility	resolutions up to SXGA		
Interface	Computer in (D-sub 15pin)	× I (Share with component	ent)	
	Monitor out (D-sub 15pin)	×I		
	Composite Video in (RCA)	×I		
	S-Video in (Mini DIN 4pin)	×I		
	HDMI (1.4a)	x2 (one share with MHI	2.0)	
	Audio in (Mini Jack)	x l		
		~ '		
	Audio L/R in (RCA)	хI		
	Audio out (Mini Jack)	×I		
	Speaker	10W x 1		
	USB (Type mini B)	x I (Download & Page u	ıp/ down)	
	USB (Type A)	x1 (1.5A power supply)		
	RS232 (DB-9pin)	RS232 (DB-9pin) x l		
	IR Receiver	x2 (Front+Top)		
Dimensions	Dimensions($W \times H \times D$)	287.3 x 114.4x 232.6 r	nm	
	Weight	2.6KG		
Power	Power Supply	AC100 to 240 V, 50 to	60 Hz	
	Power Consumption	Normal 305W. Eco 220	W. Standby <0.5W	
	Power Management Function	Automatic power off aft	er 20 minutes without a display source.	
Audible Noise	33/28 dBA (Normal/Economic mode)			
On-Screen Display Languages				
Universitie Display Languages				
	Polish/ Portuguese/ Romanian/ Russian/ Simplified	-	ek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ ai/ Traditional Chinese (28 Languages)	
Picture Modes	**Bright / Presentation / sRGB / Cinema / (3D)			
Accessories	Standard	Optional		
	Remote Control w/ Battery	Presentation Plus	P/N: 65.J9306.002	
	Power Cord (by region)	Spare Lamp Kit	P/N: 5J.JAR05.001	
	User Manual CD	Ceilling Mount	P/N: 5J.J2K01.001	
	Quick Start Guide	3D Glasses	P/N: 5J.J9H25.001	
	Warranty Card (by region)	Carry bag		
	VGA(D-sub 15pin) Cable	, ,		


*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

** Default mode is **Presentation**. When 3D is on, Picture Modes only shows 3D. When 3D is off, it is not shown in Picture Modes.


MW632ST Digital Projector

Distance Chart

Screen size			Distance from screen (mm)					
Diagonal		w		Min length		Max length	Vertical offset	
Inch	mm (mr	nch mm	(mm)	H (mm)	(max. zoom)	Average	(min. zoom)	(mm)
40	1016	862	538	625	688	750	13	
60	1524	1292	808	938	1031	1125	20	
80	2032	1723	1077	1250	1375	1500	27	
100	2540	2154	1346	1563	1719	1875	34	
120	3048	2585	1615	1875	2063	2250	40	
140	3556	3015	1885	2188	2406	2625	47	
160	4064	3446	2154	2500	2750	3000	54	
180	4572	3877	2423	2813	3094	3375	61	
200	5080	4308	2692	3125	3438	3750	67	
250	6350	5385	3365	3906	4297	4688	84	
300	7620	6462	4039	4688	5156	5625	101	



Wall mount/Ceiling mount Chart



Dimension

